

# Food Processing Industry

## Lubricants for Chains

Application	Product Recommendation	ISO VG	Viscosity Index	Service Temperature		Base Oil	NSF H1 Registration number
				From °C	To °C		
High Temperatures up to 250 °C	Lubriplate FMO-AW 150	32	107	-29	204	USP White Mineral Oil	132661
	Lubriplate FMO-AW 350	68	102	-23	249	USP White Mineral Oil	122665
	Lubriplate FMO-AW 500	100	101	-15	260	USP White Mineral Oil	122664
	Lubriplate HTCL FG 220	220	224	-	302	Ester	143870
	Lubriplate PGO FGL 150	150	232	-47	284	PAG	141192
Low Temperatures Down to -45 °C	Lubriplate SFGO Ultra 32	32	130	-57	193	PAO	125680
	Lubriplate SFGO Ultra 15	15	129	-57	241	PAO	128420
Medium Temperatures up to 160 °C	Lubriplate SFGO Ultra 460	460	159	-40	249	PAO	125541
	Lubriplate FMO-AW 85	22	107	-34	174	USP White Mineral Oil	122670
	Lubriplate FMO-AW 150	32	107	-29	204	USP White Mineral Oil	132661
Humid Areas , Conveyor Belts	Molydal NS 40 AL	-	-	-20	160	Mineral Oil	128224
	Molydal NS 50 AL	-	-	-50	160	Mineral Oil	128225
	Molydal Filmore AL	-	-	-20	180	Synthetic Oil	142222
	Molydal USAGOL AL	-	-	-20	200	Mineral Oil	130364
	Lubriplate HTCL FG 220	220	224	-	302	Ester	143870