

# Food Processing Industry

## Lubricating Greases For Gearboxes and Centralised Lubricating System

Application	Product Recommendation	NLGI Grade DIN 51818	Service Temperature		Base Oil Viscosity 40 °C (mm <sup>2</sup> / s) approx.	Base Oil	Thickner	NSF H1 Registration number
			From °C	To °C				
Gears and Centralised Lubricating System	Lubriplate Syn. Extreme FG 0	0	-40	315	90 To 110	PAO	Calcium Sulfonate Complex	137239
	Lubriplate Syn. Extreme FG 1	1	-40	315	90 To 110	PAO	Calcium Sulfonate Complex	137238
	Lubriplate Syn. Extreme FG 1/220	1	-	260	198 To 242	PAO	Calcium Sulfonate Complex	142237
	Lubriplate FGL 00	00	-	210	105	USP White Mineral Oil	Aluminium Complex	043532
Multipurpose Lubricating grease	Lubriplate Syn. Extreme FG 0	0	-40	315	90 To 110	PAO	Calcium Sulfonate Complex	137239
	Lubriplate FGL 0	0	-	224	105	USP White Mineral Oil	Aluminium Complex	043531
	Lubriplate FGL 00	00	-	210	105	USP White Mineral Oil	Aluminium Complex	043532