

Food Processing Industry

Lubricating Oils For Gears and Bearings

Application	Product Recommendation	ISO VG	Viscosity Index	Service Temperature		Base Oil	NSF H1 Registration number
				From °C	To °C		
Low Temperatures down to -45 °C	Lubriplate SFGO Ultra 32	32	130	-57	193	PAO	125680
	Lubriplate SFGO Ultra 15	15	129	-57	241	PAO	128420
Normal Temperatures up to 120 °C	Lubriplate SFGO Ultra 150	150	141	-41	257	PAO	125683
	Lubriplate SFGO Ultra 220	220	146	-42	271	PAO	125539
	Lubriplate SFGO Ultra 320	320	152	-40	271	PAO	125540
	Lubriplate SFGO Ultra 460	460	159	-40	249	PAO	125541
	Lubriplate SFGO Ultra 680	680	157	-43	260	PAO	125542
High Temperatures up to 160 °C	Lubriplate PGO FGL 150	150	232	-47	284	PAG	141192
	Lubriplate PGO FGL 220	220	242	-42	284	PAG	141193
	Lubriplate PGO FGL 320	320	252	-39	282	PAG	141194
	Lubriplate PGO FGL 460	460	262	-36	284	PAG	141195
	Lubriplate PGO FGL 680	680	272	-33	287	PAG	141196